# **Veeam - Database**

This tutorial enables you to activate the monitoring of Veeam backups on Galaxy and Infinity. You need to go through the Universe central server as Unity cannot do this natively.

To enable Esia to connect to the VeeamBackup database, you need to :

- Enable SQL and Windows authentication.
- Create a user for Esia with READ-ONLY rights.
- Check the listening port

The first 2 operations listed below are performed using the "Microsoft SQL Server Management Studio" application on the machine containing the Veeam database. And the last in the "Sql Server Configuration Manager" application.

### **SQL Server Management Studio**

### Enable SQL and Windows authentication

Right-click on property in the left-hand menu. Then, in the "security" section. Tick "SQL Server and Windows authentication mode", then click OK.

Eichier Edition Affichage Déboguer Qutils	Fenêtre <u>A</u> ide					
🕴 🖸 🔹 🕲 🗧 🔛 🔐 🗎 🕅 Nouv	ele requête 🗿 🗟 🗟 🟫 📾 🖓 🕹 🗇 🏦 🂙	- ( - )	<ul> <li>Débogueur générique *</li> </ul>	- 5	· 🛛 🗲 🟛 🗐 - 🖕	
Durier golden generalize gelooper golde Connector - Consciones Securité S	Fenigre Add ele requête De Constant of the Con			-	- 同 <b>产                                  </b>	
	Progression Pret	Chanage des proprietes des dases de données douces	OK Annuler			

### Create a user for Esia

. Microcoft EOL Environ Management Etudio (Ada

Right-click on "Security" in the left-hand menu. Go to "New" and then "User". Now fill in the user name + password. It is advisable to uncheck "Apply password expiry". Finally, select VeeamBackup as the default database.

🛃 Microsoft SQL Server Management Studio (Administrateur) Ficher Edition Affichage Déboguer Outis Fenêtre Alde	2 時間 昭 1 米 日 日   シ・ペー	- 8	<ul> <li>Gji Débogueur générique *</li> </ul>	- 5	- 🕢 🗲 🛥 🗐 - 📮
Explorateur d'objets  Connector  Sector  Secto	Propriétés de la connexion Selectionner une para P Générie Magage de fuilisatur De Eléments sécuritables P Elements sécuritables P Elem	esia Script • Aide Non d'accès: Catiget Authentification Windows C Authentification SQL Server Mol de passe: Confirme le statégie de mol de pass Confirme le statégie de mol de pass C Mappe au certificat C Mappe à la céé asymétrique Mapper aux informations didentification		X	
	Srivčkavvečkavsol,2006R2 Convesion: SRIVEAMAdministrateur v∳ Allichet let propietišt de com Progression Progression Pret	Informations d'identification mappées Base de données par défaut : Langue par défaut :	Informations Fournisseur Supprimer English T OK Annuler		

### Assign read-only rights to this user

In the user properties, go to "User mapping" and check that VeeamBackup is ticked. And select the following rights:

- db\_datareader
- public

TXX The osore set set ver than agement sea	no (nanninscracear)								
Fichier Edition Affichage Déboguer Out	ils Fenêtre Aide								
💿 - 💿   🏠 - 🖆 - 🚔 🔛 🚰   🗿 No	uvelle requête 🛛 🗟 🗟	Ala とうもう・C	- 8	-	*	Débogueur générique	-	- 5	•
Evolorateur d'objets									
E SRVVEAMVEEAMSOL2008R2 (SOL Server									
🐨 🛑 Bases de données		Propriétés de la connexion -	esia						
🖃 🛑 Sécurité		Sálastissper upo page	<b>T a i a</b>	0.00					
🖃 📁 Connexions		Général	L Script -	• 😲 Aide					
💑 ##M5_PolicyEventProcessingL		& Bôles du serveur							
🙀 ##MS_PolicyTsqlExecutionLogi		Appage de l'utilisateur	Utilisateu	rs mappés à cette connexi	on :				
AUTORITE NT\Systeme		Éléments sécurisables	Mapp	Base de données	Utilisateur	Schéma par défaut			
BUILTIN/Administrateurs		🔎 État		master					
BOMDECIKH)Administrateur				model					
esia				msdb					
NI SERVICE\MSSQL\$VEEAMSQ				tempdb					
嶷 sa				VeeamBackup	esia	dbo			
SRVVEAM\Administrateur					muund				
Röles du serveur									
Objets serveur									
Béplication									
Gestion									
		Connexion	Comp	ste Invité activé nour : Vee	amRaekun				
		Serveur :	i counte	ne mine source pour . ree					
		SRVVEAM\VEEAMSQL2008R2	Apparten	iance au rôle de base de d	onnées : VeeamBackup				
		Connexion :	🗌 db ə	ccessadmin					
		SHVVEAMVAdministrateur	db D	ackupoperator					
		VY Afficher les propriétés de conr	( db_d	atareader					
				atawriter					
				uaumin Ienvdatareader					
			db_d	lenydatawriter					
		Progression	□ db_o	wner					
		Prêt	d db a	ecurityadmin					
		S. 2	Public	9					
		LL							
						OK	Annuler		
-							-		

## Sql Server Configuration Manager

Now go to the SQL Server Configuration Manager.

In the tree on the right, scroll down to "SQL Server Network Configuration" and click on "Protocols for VEEAMSQLXXXX".

Then right-click on TCP/IP and open the properties. In the "IP addresses" tab, go to the bottom of the drop-down list. You can indicate or check that the TCP Port value is set to 1433.



If necessary, you will need to restart the SQL service.

### **Configuration on Esia**

### Esia Galaxy only

You need to activate the Esia backup webplugin. To do this, connect to the Esia server using ssh (Putty) and enter the following command as root: apt-get update && apt-get install esia-webp-backup

### Add a backup node.

In your Esia interface, go to administration (the toothed road on the left) and then click on the

#### "manually add node" button in the top right-hand corner. As shown in the image below.

Ø					ł	TAT DES 36 5	15 2 <sup>E</sup> S	TAT DES ERVICES 340	9 27	34	2
	BONJOUR SALOC Accueil >	Administration							2	•	
<u> </u>	GROUPES DE NOEUDS		PES DE NOEUDS 👌 PLU				🛞 LOG				
	RACINE + CLIENT 1 + CLIENT 2	NOEUDS							(74)	>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>	•
	CLIENT 3 CLIENT 4 CLIENT 5	NOM DU NOEUD	GROUPE \$	TYPE DE NOEUD 🗘	ADRESSE IP 0	DESCRIPTIO	× 2 °	NOMBRE DE SERVICES	≎ ACTI	ON	
	CLIENT 6										
	CLIENT 8 PASTOUCHE	Accès Internet	Applications	none	10.8.0.11			3	۵		
	WEB	app-anscan	Applications	application	0.0.0.0			1	۵ 💼		
		BCK-Bareos-director	Backup	backup server	10.7.0.7			6	۵		
•		BCK-Eurobackup-server	Backup	backup server	10.7.0.9			3	۵		
		BCK-Mail Analyzer	Backup	none	0.0.0.0	Analyse d'une boite mails rece backups.	vant le résultat de	1	۵		
۲	1	BCK-Veeam-server	Backup	backup server	10.7.0.8			5	۵.		
		Capteur de température	Salle serveur	none	10.5.0.250	RACK-LOCAL5		6	۵		
		cl-1-wan-siteB	Pare-feux	none	8.8.8.8			1	۵		
		cl1-erp	Applications	application	0.0.0.0			1	۵ 🗊		
		cl1-maintenance	Maintenance	none	10.13.0.150			1	۵		
		cl1-réseau	Applications	application	0.0.0.0			1			

### The following page appears:

OUTER UN NOEUD		
INFORMATIONS GÉNÉRALES		
Nom du noeud	Type de noeud	Groupe
veeam	Backup server	<ul> <li>Sélectionner le(s) groupe(s) au(x)quel(s) ce noeud a</li> </ul>
Adresse IP	Connecté derrière la Unity:	
10.12.0.3	none	Y
Description		
		rm.
INFORMATIONS SIMP		
Version SNMP		
none	Ť	
		Ajout

Specify the name, IP address and group in which the node should appear. **The most important thing is to indicate the type of node, such as "backup server".** A configuration page will appear, asking you to configure the driver. Select the "veeam - db" driver and a menu will appear below it. Click on "SQL Authentication" and enter your database connection parameters.

#### 2025/05/13 09:15

JOUTER UN NOEUD				×
				_
CONFIGURATION DU DRIVER				
Driver	Durée de rétention (En jours)			
veeam - db	* 15	•		
Authentification SQL Authentific	ion Windows			
1433				
Base de données				
veeamdb				
Utilisateur				
esia				
Mot de passe				
			Annuler Test	Sauver

Once you have filled in the details, click on 'Test' to validate your user parameters. If the test is OK, you can save it.

You now need to wait 15 to 30 minutes for synchronisation to take place. Once synchronisation is complete, you can start monitoring your backups. You can continue the tutorial by following this link: Activate back-up monitoring

From: https://wiki.esia-sa.com/ - **Esia Wiki** 

Permanent link: https://wiki.esia-sa.com/en/advanced/sql\_veeam

Last update: 2023/11/09 18:06

